



## PART NUMBER STRUCTURE

<b>G3</b>		<b>XX</b>	-	<b>X</b>	-	-	-	-
<b>METER SIZE</b>								
	4" Meter	04						
	6" Meter	06						
	8" Meter	08						
	10" Meter	10						
	12" Meter	12						
<b>OUTSIDE DIAMETER (O.D.) RANGE</b>		<b>MUST SPECIFY :</b>		<b>X</b>				
<b>4" METER</b>	3.90 - 4.14"			0				
	4.35 - 4.64"			1				
	4.65 - 4.90"			2				
	4.91 - 5.15"			3				
<b>6" METER</b>	5.50 - 5.89			1				
	5.90 - 6.75			2				
	6.76 - 7.49			3				
<b>8" METER</b>	7.50 - 7.79			3				
	7.80 - 8.93			4				
	8.94 - 9.19			5				
<b>10" METER</b>	9.20 - 9.69			5				
	9.70 - 10.94			6				
	10.95 - 11.29			7				
<b>12" METER</b>	11.30 - 11.69			7				
	11.70 - 12.94			8				
	12.95 - 13.39			9				
<b>POWER / OUTPUT OPTIONS</b>								
	Battery Power / No Outputs ( Default )			-				
	Battery Power / Pulse Output			1	0	•	•	
	DC Power (10-32v) / 4-20mA Output			2	•	0	•	
	DC Power (10-32v) / 4-20mA Output / Pulse Output			3	•	•	•	
<b>POWER CABLE LENGTH OPTIONS</b>								
	No Cable - Output configured [Quick Connect Only]			0				
	6ft (Open Leads - Hardwired only) [Default]			1				
	25ft (Open Leads)			2				
	50ft (Open Leads)			3				
<b>PULSE CABLE LENGTH OPTIONS</b>								
	No Cable - Output configured [Quick Connect Only]			0				
	6ft (Open Leads - Hardwired only) [Default]			1				
	25ft (Open Leads)			2				
	50ft (Open Leads)			3				
	25ft (7-Pin Male Connector for Telemetry Output)			4				
	50ft (7-Pin Male Connector for Telemetry Output)			5				
<b>OUTPUT CABLE TERMINAL OPTIONS</b>								
	Open Leads ( Hardwired )							1
	Quick Connection Cable Terminals (25 and 50 ft length only on meter mount converter)							2
<b>DATA LOGGER Standard Feature</b>								
	Internal Data Logger							